**SDS Revision Date:** 

08/23/2018



### 1. Identification

1.1. Product identifier

Product Identity

Glass Pro, Aerosol Glass Cleaner

Alternate Names

Glass Pro, Aerosol Glass Cleaner

LHB Part Number: 0164---000

National Stock Number: 7930-01-513-6864

CAGE Code: 0FTT5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Product LabelApplication MethodSee Product Label

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

**Emergency** 

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

## 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222 Extremely flammable aerosol.

Skin Irrit. 3;H316 Causes mild skin irritation. (Not adopted by US OSHA)

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger** 

**SDS Revision Date:** 

08/23/2018



H222 Extremely flammable aerosol.

H316 Causes mild skin irritation.

#### [Prevention]:

No GHS prevention statements

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

#### [Response]:

P332+313 If skin irritation occurs: Get medical advice / attention.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

#### [Disposal]:

No GHS disposal statements

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations                            | Weight % | GHS Classification   | Notes  |
|---|----------|--|--------|
| Isopropyl Alcohol<br>CAS Number: 0000067-63-0               | 1.0 - 10 | Flam. Liq. 2;H225<br>Eye Irrit. 2;H319<br>STOT SE 3;H336   | [1][2] |
| Propane, 2-methyl-<br>CAS Number: 0000075-28-5              | 1.0 - 10 | Flam. Gas 1;H220<br>Press. Gas;H280  | [1][2] |
| Butane<br>CAS Number: 0000106-97-8                          | 1.0 - 10 | Flam. Gas 1;H220<br>Press. Gas;H280  | [1][2] |
| Ethylene glycol monobutyl ether<br>CAS Number: 0000111-76-2 | 1.0 - 10 | Acute Tox. 4;H332<br>Acute Tox. 4;H312<br>Acute Tox. 4;H302<br>Eye Irrit. 2;H319<br>Skin Irrit. 2;H315 | [1][2] |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

<sup>[1]</sup> Substance classified with a health or environmental hazard.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.
\*The full texts of the phrases are shown in Section 16.

LIGHTHOUSE for the BLIND

**SDS Revision Date:** 

08/23/2018

### 4. First aid measures

### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** ROUTES OF EXPOSURE: Exposure may be by INHALATION and/or SKIN or EYE

contact, depending on conditions of use. To minimize exposure, follow recommendations

for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE: Irritation of eyes, skin and upper respiratory system.

May cause damage to liver and kidneys.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness

and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin,

eye, liver, kidney and lymphatic disorders.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatique, muscular

weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation

and soreness with possible reversible damage. See section 2 for further details.

**Skin** Causes mild skin irritation. (Not adopted by US OSHA)

**SDS Revision Date:** 

08/23/2018



### 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Do not use: water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 126

#### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

LIGHTHOUSE for the BLIND

SDS Revision Date:

08/23/2018

### 7. Handling and storage

#### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Caustics. Acids. Oxidizers.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

#### 8.1. Control parameters

#### **Exposure**

| CAS No.                         | Ingredient                      | Source               | Value   |
|---------------------------------|---------------------------------|----------------------|---|
| 0000067-63-0 Isopropyl Alcohol  | Isopropyl Alcohol               | OSHA                 | TWA 400 ppm (980 mg/m3)STEL 500 ppm             |
|                                 |                                 | ACGIH                | TWA: 200 ppm STEL: 400 ppm Revised 2003,        |
|                                 |                                 | NIOSH                | TWA 400 ppm (980 mg/m3) ST 500 ppm (1225 mg/m3) |
|                                 |                                 | Supplier             | No Established Limit                            |
| 0000075-28-5 Propane, 2-methyl- | Propane, 2-methyl-              | OSHA                 | No Established Limit                            |
|                                 |                                 | ACGIH                | STEL: 1000ppm                                   |
|                                 |                                 |                      | TWA 800 ppm (1900 mg/m3)                        |
|                                 | Supplier                        | No Established Limit |   |
| 0000106-97-8 Butane             | Butane                          | OSHA                 | No Established Limit                            |
|                                 |                                 | ACGIH                | TWA: 600 ppm STEL: 750 ppm                      |
|                                 |                                 | NIOSH                | TWA 800 ppm (1900 mg/m3)                        |
|                                 |                                 | Supplier             | No Established Limit                            |
| 0000111-76-2 Eth                | Ethylene glycol monobutyl ether | OSHA                 | TWA 50 ppm (240 mg/m3) [skin]                   |
|                                 |                                 | ACGIH                | TWA: 20 ppmRevised 2003,                        |
|                                 |                                 | NIOSH                | TWA 5 ppm (24 mg/m3) [skin]                     |
|                                 |                                 | Supplier             | No Established Limit                            |

**SDS Revision Date:** 

LIGHTHOUSE for the BLIND

08/23/2018

#### Carcinogen Data

| CAS No.                                      | Ingredient | Source   | Value   |  |  |
|--|------------|--|---|--|--|
| 0000067-63-0 Isopropyl Alcohol               |            | OSHA   | Select Carcinogen: No   |  |  |
|  |            | NTP  | Known: No; Suspected: No  |  |  |
|  |            | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |  |  |
| 0000075-28-5 Propane, 2-methyl-              |            | OSHA   | Select Carcinogen: No   |  |  |
|  | NTP        | Known: No; Suspected: No   |   |  |  |
|  | IARC       | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |   |  |  |
| 0000106-97-8 Butane                          |            | OSHA   | Select Carcinogen: No   |  |  |
|  | NTP        | Known: No; Suspected: No   |   |  |  |
|  | IARC       | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |   |  |  |
| 0000111-76-2 Ethylene glycol monobutyl ether |            | OSHA   | Select Carcinogen: No   |  |  |
|  |            | NTP  | Known: No; Suspected: No  |  |  |
|  |            | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |  |  |

#### 8.2. Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

**Eyes** Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.

**Skin** Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

Appearance Colorless Liquid

Odor Pleasant
Odor threshold Not Measured

pH approximately 9
Melting point / freezing point Not Measured
Initial boiling point and boiling range Not Measured

**SDS Revision Date:** 

08/23/2018



Flash Point -156 F (Propellant)
Evaporation rate (Ether = 1) slower than ether

Flammability (solid, gas)

Flam. Aerosol 1; H222 Extremely flammable aerosol.

Upper/lower flammability or explosive limits

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Vapor pressure (Pa) Not Measured

Vapor Density > 1

Specific Gravity 0.948 (7.90 lb/gal)

Solubility in Water Soluble

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

VOC Content

Not Measured

HAPS (lbs/gal) 0.0
HAPS (lbs/gal of Solids) 0.0
HAPS (lbs/lb of Solids) 0.0

% Volatile (by volume) Not Measured

9.2. Other information

No other relevant information.

## 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Do not mix with alkalis.

#### 10.5. Incompatible materials

Caustics, Acids, Oxidizers,

#### 10.6. Hazardous decomposition products

Oxides of Carbon

**SDS Revision Date:** 

08/23/2018



### 11. Toxicological information

#### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

| Ingredient                                   | Oral LD50,<br>mg/kg                      | Skin LD50,<br>mg/kg                      | Inhalation<br>Vapor LC50,<br>mg/L/4hr   | Inhalation<br>Dust/Mist LC50,<br>mg/L/4hr | Inhalation<br>Gas LC50,<br>ppm |
|--|--|--|---|---|--------------------------------|
| Isopropyl Alcohol - (67-63-0)                | 4,710.00, Rat -<br>Category: 5           | 12,800.00, Rat -<br>Category: NA         | 72.60, Rat -<br>Category: NA            | No data available                         | No data<br>available           |
| Propane, 2-methyl (75-28-5)                  | No data available                        | No data available                        | 658.00, Rat -<br>Category: NA           | No data available                         | No data available              |
| Butane - (106-97-8)                          | No data available                        | No data available                        | 658.00, Rat -<br>Category: NA           | No data available                         | No data<br>available           |
| Ethylene glycol monobutyl ether - (111-76-2) | 1,414.00,<br>Guinea Pig -<br>Category: 4 | 1,200.00,<br>Guinea Pig -<br>Category: 4 | 173.00, Guinea<br>Pig - Category:<br>NA | No data<br>available                      | No data<br>available           |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification                | Category | Hazard Description                                    |
|-------------------------------|----------|---|
| Acute toxicity (oral)         |          | Not Applicable  |
| Acute toxicity (dermal)       |          | Not Applicable  |
| Acute toxicity (inhalation)   |          | Not Applicable  |
| Skin corrosion/irritation     | 3        | Causes mild skin irritation. (Not adopted by US OSHA) |
| Serious eye damage/irritation |          | Not Applicable  |
| Respiratory sensitization     |          | Not Applicable  |
| Skin sensitization            |          | Not Applicable  |
| Germ cell mutagenicity        |          | Not Applicable  |
| Carcinogenicity               |          | Not Applicable  |
| Reproductive toxicity         |          | Not Applicable  |

**SDS Revision Date:** 

08/23/2018



| STOT-single exposure   | <br>Not Applicable |
|------------------------|--------------------|
| STOT-repeated exposure | <br>Not Applicable |
| Aspiration hazard      | <br>Not Applicable |

## 12. Ecological information

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

#### **Aquatic Ecotoxicity**

| Ingredient                                   | 96 hr LC50 fish,<br>mg/l         | 48 hr EC50 crustacea,<br>mg/l | ErC50 algae,<br>mg/l                    |
|--|----------------------------------|-------------------------------|---|
| Isopropyl Alcohol - (67-63-0)                | 1,400.00, Lepomis<br>macrochirus | 100.00, Daphnia magna         | 100.00 (72 hr), Scenedesmus subspicatus |
| Propane, 2-methyl (75-28-5)                  | Not Available                    | Not Available                 | Not Available                           |
| Butane - (106-97-8)                          | 6.00, Fish (Piscis)              | Not Available                 | Not Available                           |
| Ethylene glycol monobutyl ether - (111-76-2) | 220.00, Fish (Piscis)            | 1,000.00, Daphnia magna       | Not Available                           |

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

#### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

**SDS Revision Date:** 

08/23/2018

### 14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) Transportation)

**14.1. UN number** UN1950 UN1950 UN1950

**14.2. UN proper** Aerosols, flammable, Aerosols, flammable, Shipping name (each not exceeding 1 L capacity) Aerosols, flammable, (each not exceeding 1 L

capacity) capacity)

**14.3.** Transport DOT Hazard Class: 2.1 IMDG: 2.1 Air Class: 2.1 hazard class(es)

**14.4. Packing** Not Applicable Not Applicable Not Applicable

group

14.5. Environmental hazards

**IMDG** Marine Pollutant: No

14.6. Special precautions for user

No further information

### 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

**Toxic Substance** All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification Not Regulated F

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: Yes

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): No

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Ethylene glycol monobutyl ether

Isopropyl Alcohol

#### Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**SDS Revision Date:** 

08/23/2018



#### **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **New Jersey RTK Substances (>1%):**

Butane

Ethylene glycol monobutyl ether

Isopropyl Alcohol

Propane, 2-methyl-

#### Pennsylvania RTK Substances (>1%):

**Butane** 

Ethylene glycol monobutyl ether

Isopropyl Alcohol

Propane, 2-methyl-

#### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or

**SDS Revision Date:** 

08/23/2018



completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

**End of Document**