



Safety Data Sheet SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

1. Identification

1.1. Product identifier

Product Identity

SO-SURE Primer Aerosol

Alternate Names

Specification: A-A-1552A Brown 30109
LHB Part Number: 0244---314
National Stock Number: 8010-00-067-5434
CAGE Code: 0FTT5
Contract Number: GS-10F-40786

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Product Label

1.3. Details of the supplier of the safety data sheet

Company Name

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No.

(800) 633-8253 (PERS)

Customer Service: LHB Industries

(314) 423-4333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222	Extremely flammable aerosol.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Eye Dam. 2A;H319	Causes serious eye irritation.
Muta. 1B;H340	May cause genetic defects.
Carc. 1B;H350	May cause cancer.
STOT SE 3;H336	May cause drowsiness or dizziness.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.

2.2. Label elements



Danger



Safety Data Sheet SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapor.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness and dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H411 Toxic to aquatic life with long lasting effects.
May displace oxygen and cause rapid suffocation.
Pressurized container: May burst if heated.

[Prevention]:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
P211 Do not spray on an open flame or other ignition source.
P233 Keep container tightly closed.
P240 Ground, bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, light, equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust, fume, gas, mist, vapors, spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.
P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P308+313 IF exposed or concerned: Get medical advice or attention.
P331 Do NOT induce vomiting.
P337+313 If eye irritation persists: Get medical advice or attention.
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.
P391 Collect spillage.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.
P405 Store locked up.



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C , 122 °F.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 0000067-64-1	34.06	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
N-Butyl Acetate CAS Number: 0000123-86-4	17.11	Flam. Liq. 3;H226 STOT SE 3;H336	----
Propane CAS Number: 0000074-98-6	14.25	Flam. Gas 1;H220	----
Butane CAS Number: 0000106-97-8	6.33	Flam. Gas 1;H220	----
Magnesium silicate talc CAS Number: 0014807-96-6	6.17	Not Classified	----
Naphtha (petroleum), hydrotreated light CAS Number: 0064742-49-0	5.66	Asp. Tox. 1;H304 Muta. 1B;H340 Carc. 1B;H350	----
Isobutane CAS Number: 0000075-28-5	2.92	Flam. Gas 1;H220 Press. Gas;H280	----
Iron oxide CAS Number: 0001332-37-2	1.93	Not Classified	----
Phosphoric acid, zinc salt (2:3) CAS Number: 0007779-90-0	1.40	Aquatic Acute 1;H400 Aquatic Chronic 1;H410	----
Iron hydroxide oxide yellow CAS Number: 0051274-00-1	0.81	Not Classified	----
Stoddard solvent CAS Number: 0008052-41-3	0.64	STOT RE 1;H372 Asp. Tox. 1;H304	----

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
4.2. Most important symptoms and effects, both acute and delayed	
Overview	EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness, staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. Reproductive or genetic defect hazard. Treat symptomatically. Check section 2.2 (GHS Label Elements) for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 126



Safety Data Sheet SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong acids and oxidizing materials

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m3) STEL 2400 mg/m3
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m3) TWA
0000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m3)
		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
0000075-28-5	Isobutane	OSHA	No Established Limit



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

		ACGIH	1000 ppm STEL (explosion hazard, listed under Butane, isomers)
		NIOSH	TWA 800 ppm (1900 mg/m3)
0000106-97-8	Butane	OSHA	No Established Limit
		ACGIH	TWA: 600 ppm STEL: 750 ppm
		NIOSH	TWA 800 ppm (1900 mg/m3)
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m3)
		ACGIH	TWA: 150 ppm, STEL 200 ppm
		NIOSH	TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3)
0001332-37-2	Iron oxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0007779-90-0	Phosphoric acid, zinc salt (2:3)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m3)
		ACGIH	TWA: 290 mg/m3 STEL: 580 mg/m3
		NIOSH	TWA 350 mg/m3 C 1800 mg/m3 [15-minute]
0014807-96-6	Magnesium silicate talc	OSHA	TWA 20 mppcf
		ACGIH	Containing asbestos fibres TWA: 0.1 f/cc (K) A1, 1 Containing no asbestos fibres TWA:2 mg/m3 (E) (respirable)
		NIOSH	TWA 2 mg/m3 (resp)
0064742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

8.2. Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.
- Skin** Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

Section 9. Physical and chemical properties



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

9.1. Information on basic physical and chemical properties

Appearance	Brown Liquid/Gas
Odor	Solvent
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	-156F (Propane)
Evaporation rate (Ether = 1)	Slower than ether
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.1 Upper Explosive Limit: 12.8
Vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than Air
Relative Density	0.798
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	581 g/l (4.85 pounds/gal.), less water and exempt solvents
% Volatile (by volume)	Not Measured

9.2. Other information

No other relevant information.

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Strong acids and oxidizing materials

10.6. Hazardous decomposition products



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

Oxides of Carbon

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Magnesium silicate talc - (14807-96-6)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Naphtha (petroleum), hydrotreated light - (64742-49-0)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available	No data available	No data available
Isobutane - (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Iron oxide - (1332-37-2)	No data available	No data available	No data available	No data available	No data available
Phosphoric acid, zinc salt (2:3) - (7779-90-0)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
0000074-98-6	Propane	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

0000075-28-5	Isobutane	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000106-97-8	Butane	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0001332-37-2	Iron oxide	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0007779-90-0	Phosphoric acid, zinc salt (2:3)	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0014807-96-6	Magnesium silicate talc	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	A4
0064742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	1B	May cause genetic defects.
Carcinogenicity	1B	May cause cancer.



Safety Data Sheet SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Section 12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00 (96 hr), Pseudokirchneriella subcapitata
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.00 (72 hr), Pseudokirchnerella subcapitata
Propane - (74-98-6)	49.90, Fish	69.43, Daphnia sp	19.37 (72 hr), Algae
Butane - (106-97-8)	49.90, Fish (Piscis)	69.43, Daphnia sp	19.37 (96 hr), Algae
Magnesium silicate talc - (14807-96-6)	, Fishes species	36,812.36, Daphnid species	7,202.70 (96 hr), Green algae
Naphtha (petroleum), hydrotreated light - (64742-49-0)	Not Available	2.60, Chaetogammarus marinus	Not Available
Isobutane - (75-28-5)	Not Available	Not Available	Not Available
Iron oxide - (1332-37-2)	Not Available	Not Available	Not Available
Phosphoric acid, zinc salt (2:3) - (7779-90-0)	0.09, Oncorhynchus mykiss	0.04, Daphnia magna	0.136 (72 hr), Selenastrum capricornutum
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

Section 13. Disposal considerations



Safety Data Sheet SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1950	UN1950	UN1950
14.2. UN proper shipping name	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1	IMDG: 2.1 Sub Class: Not Applicable	Air Class: 2.1
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes; (Phosphoric acid, zinc salt (2:3))		
14.6. Special precautions for user	Not Applicable		

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

EPCRA 302 Extremely Hazardous:
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:
Phosphoric acid, zinc salt (2:3)

Proposition 65 - Carcinogens (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:
This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



Safety Data Sheet

SO-SURE Primer Aerosol

SDS Revision
Date: 09/04/2020

Section 16. Other information

SDS Revision Date 09/04/2020

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document