

SDS Revision Date: 02/08/2021

1. Identification

1.1. Product identifier

Product Identity Metered Mist Vanilla Bean 0744---004

Alternate Names Metered Mist Vanilla Bean 0744---004

LHB Part Number: 0744---004

CAGE 0FTT5

National Stock Number: 6840-01-429-5864

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Air Freshener

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222 Extremely flammable aerosol.

Press. Gas;H280 Contains gas under pressure; may explode if heated.

Flam. Liq. 1;H224 Extremely flammable liquid and vapor.

Eye Dam. 2A;H319 Causes serious eye irritation.

STOT SE 3;H336 May cause drowsiness or dizziness.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

2.2. Label elements



Danger

H222 Extremely flammable aerosol.

H224 Extremely flammable liquid and vapor.



SDS Revision Date: 02/08/2021

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

May displace oxygen and cause rapid suffocation.

Pressurized container: May burst if heated.

[Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P233 Keep container tightly closed.

P240 Ground, bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust, fume, gas, mist, vapors, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P337+313 If eye irritation persists: Get medical advice or attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C , 122 °F.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 0000067-64-1	1	Flam. Liq. 2;H225 Eye Irrit. 2;H319	



SDS Revision Date: 02/08/2021

		STOT SE 3;H336	
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220	
1,2-Propanediol CAS Number: 0000057-55-6	5 - 10	Not Classified	
Ethanol CAS Number: 0000064-17-5	1 - 5	Flam. Liq. 2;H225	
Benzyl benzoate CAS Number: 0000120-51-4	1 - 5	Acute Tox. 4;H302 Aquatic Chronic 2;H411	

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious, place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component

solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of

consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements)

for further details.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



SDS Revision Date: 02/08/2021

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Keep container tightly closed.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust, fume, gas, mist, vapors, spray.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 126

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.



SDS Revision Date: 02/08/2021

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000057-55-6	1,2-Propanediol	OSHA	No Established Limit
		ACGIH	TWA(Aerosol): 10 mg/m3
		NIOSH	No Established Limit
0000064-17-5	Ethanol	OSHA	TWA 1000 ppm (1900 mg/m3)
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1900 mg/m3)
0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m3) STEL 2400 mg/m3
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m3) TWA
0000074-98-6	00074-98-6 Propane		TWA 1000 ppm (1800 mg/m3)
		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
0000120-51-4	Benzyl benzoate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

Eyes Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.



SDS Revision Date: 02/08/2021

Skin Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Color: Colorless to light yellow Physical State: Liquid

Odor Vanilla

Odor threshold

pH

Not Determined

Melting point / freezing point

Initial boiling point and boiling range

Flash Point

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Not determined

Not Determined

-156°F (Propane)

Not Determined

Not Determined

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Determined

Upper Explosive Limit: Not Determined

Vapor pressure (Pa) Not Determined **Vapor Density** Not Determined **Relative Density** Not Measured Solubility in Water Not Measured Partition coefficient n-octanol/water (Log Kow) Not Measured **Auto-ignition temperature** Not Determined **Decomposition temperature** Not Determined Not Determined Viscosity (cSt) **VOC Content** <30 % by Wt. **Maximum Incremental Reactivity** Not Measured

HAPS (lbs/gal) 0.0
HAPS (lbs/gal of Solids) 0.0
HAPS (lbs/lb of Solids) 0.0
% Volatile (by volume) 100%

9.2. Other information

No other relevant information.



SDS Revision Date: 02/08/2021

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

10.6. Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
1,2-Propanediol - (57-55-6)	22,000.00, Rat - Category: NA	> 2,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Ethanol - (64-17-5)	10,470.00, Rat - Category: NA	17,100.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available



SDS Revision Date: 02/08/2021

Benzyl benzoate - (120-51-4)	3,253.00, Mouse - Category: 5	>2,000.00, Rabbit - Category: 5	No data available	No data available	No data available
	Category. 5	Category. 5			

Carcinogen Data

CAS No.	Ingredient	Source		Value			
0000057-55-6	1,2-Propanediol	OSHA	Regulated Carcinogen: No				
		NTP	Known: No:	; Suspected: No			
		IARC	Group 1: No	o; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
		ACGIH					
0000064-17-5 Ethanol		OSHA	Regulated (Regulated Carcinogen: No			
		NTP		; Suspected: No			
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
			A3				
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0000074 00 6	Dronone	ACGIH	A4	Corningment No			
0000074-98-6	Propane	NTP		Carcinogen: No			
		IARC	Known: No; Suspected: No Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
		ACGIH	No Established Limit				
0000120-51-4	Benzyl benzoate	OSHA	Regulated Carcinogen: No				
	30.129.120.120.10	NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
		ACGIH	No Established Limit				
Classification		Ca	tegory	Hazard Description			
Acute toxicity	/ (oral)			Not Applicable			
Acute toxicity	/ (dermal)			Not Applicable			
Acute toxicity	/ (inhalation)			Not Applicable			
Skin corrosic	n/irritation			Not Applicable			
Serious eye	damage/irritation		2A	Causes serious eye irritation.			
Respiratory s	sensitization			Not Applicable			
Skin sensitiz	ation			Not Applicable			
Germ cell mu	utagenicity			Not Applicable			
Carcinogenicity				Not Applicable			
Reproductive toxicity			Not Applicable				
STOT-single exposure		3	May cause drowsiness or dizziness.				
OTOT : I			Not Applicable				
STOT-repea	ted exposure			Not Applicable			
Aspiration hazard			Not Applicable				



SDS Revision Date: 02/08/2021

Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00 (96 hr), Pseudokirchneriella subcapitata
Propane - (74-98-6)	49.90, Fish	69.43, Daphnia sp	19.37 (72 hr), Algae
1,2-Propanediol - (57-55-6)	40,613.00, Salmo gairdneri	18,340.00, Ceriodaphnia dubia	24,200.00 (72 hr), Raphidocelis subcapitata
Ethanol - (64-17-5)	15,400.00, Lepomis macrochirus	> 10,000, Daphnia magna	17.921 (96 hr), Ulva pertusa
Benzyl benzoate - (120-51-4)	2.32, Danio rerio	3.09, Daphnia magna	0.475 (72 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

name

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA Transportation) **Transportation**) UN1950 UN1950 14.1. UN number UN1950 14.2. UN proper shipping UN1950, Aerosols, Limited Aerosols, Limited Quantity Aerosols, Limited Quantity, 2.1, NA Quantity



SDS Revision Date: 02/08/2021

14.3. Transport hazard

class(es)

DOT Hazard Class: 2.1 **Sub Class:** Not Applicable

IMDG: 2.1 Sub Class: Not Applicable Air Class: 2.1 Sub Class: Not Applicable

14.4. Packing group

Not Applicable

Not Applicable

Not Applicable

14.5. Environmental hazards

IMDG

Marine Pollutant: No;

14.6. Special precautions for user

Not Applicable

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance

All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

Note: Ethanol (Ethyl alcohol) has been placed on the California Proposition 65 Cancer and Developmental Lists when in alcoholic beverages.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethanol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

SDS Revision Date 02/08/2021

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.



SDS Revision Date: 02/08/2021

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H411 Toxic to aquatic life with long lasting effects.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document