

SDS Revision Date: 08/23/2018

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Refresh, Country Garden Aerosol Air Freshener

Alternate Names Specification: A-A-267C

LHB Part Number:0754---002

National Stock Number: 6840-01-359-9207

CAGE Code: 0FTT5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee product label.Application MethodSee product label.

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Gas 1;H222 Extremely flammable aerosol.

Press. Gas;H280 Contains gas under pressure; may explode if heated.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

SDS Revision Date:



08/23/2018

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

[Response]:

P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

[Storage]:

P410+403 Protect from sunlight. Store in a well ventilated place.

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Propane, 2-methyl- CAS Number: 0000075-28-5	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Butane CAS Number: 0000106-97-8	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Propane CAS Number: 0000074-98-6	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]

^[1] Substance classified with a health or environmental hazard.

4. First aid measures

4.1. Description of first aid measures

General Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.

^{*}The full texts of the phrases are shown in Section 16.

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 08/23/2018

Remove and isolate contaminated clothing and shoes.

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Keep victim warm and quiet.

Ensure that medical personnel are aware of the material(s) involved and take precautions

to protect themselves.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should

be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts

with lukewarm water.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness,

staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and

eye disorders. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Carbon Dioxide, Dry Chemical, Foam

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

LIGHTHOUSE for the BLIND

SDS Revision Date: 08/23/2018

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite. Fire may produce irritating, corrosive and/or toxic gases.

ERG Guide No. 126

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.

If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Keep out of low areas.

Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong acids and oxidizing materials

See section 2 for further details. - [Storage]:

SDS Revision Date:

08/23/2018

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000074-98-6 Propane		OSHA	TWA 1000 ppm (1800 mg/m3)
			Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
		Supplier	No Established Limit
0000075-28-5 Propane, 2-methyl-		OSHA	No Established Limit
	ACGIH	STEL: 1000ppm	
		NIOSH	TWA 800 ppm (1900 mg/m3)
	Supplier	No Established Limit	
0000106-97-8 Butane		OSHA	No Established Limit
	ACGIH	TWA: 600 ppmSTEL: 750 ppm	
		NIOSH	TWA 800 ppm (1900 mg/m3)
			No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000074-98-6	Propane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000075-28-5 Propane, 2-methyl-		OSHA	Select Carcinogen: No
			Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000106-97-8	Butane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 08/23/2018

Respiratory If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

Eyes Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.

Skin Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Milky white Liquid/Gas

Odor Floral

Odor threshold

PH

Not Measured

Flash Point

-156 F (propellant)

Evaporation rate (Ether = 1)

Slower than ether

Flammability (solid, gas) Flam. Aerosol 1;H222 Extremely flammable aerosol.

Upper/lower flammability or explosive limits Lower Explosive Limit: 1.8

Upper Explosive Limit: 9.5

Vapor pressure (Pa) Not Measured

Vapor Density >1

Specific Gravity 0.840 (7.05 lbs/gal)

Solubility in Water Soluble

Partition coefficient n-octanol/water (Log Kow)Not MeasuredAuto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)Not MeasuredVOC %20.0% by wt.

HAPS (lbs/gal) 0.0

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

SDS Revision Date: 08/23/2018

HAPS (lbs/gal of Solids) 0.0 HAPS (lbs/lb of Solids) 0.0

% Volatile (by volume) Not Measured

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Strong acids and oxidizing materials

10.6. Hazardous decomposition products

Oxides of Carbon

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Propane, 2-methyl (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



SDS Revision Date: 08/23/2018

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Propane, 2-methyl (75-28-5)	Not Available	Not Available	Not Available	
Butane - (106-97-8)	6.00, Fish (Piscis)	Not Available	Not Available	
Propane - (74-98-6)	Not Available	Not Available	Not Available	

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.



SDS Revision Date: 08/23/2018

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

name

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

DOT (Domestic Surface IMO / IMDG (Ocean ICAO/IATA

Transportation) Transportation)

14.1. UN number UN1950 UN1950 UN1950

UN1950, Aerosols, Limited Aerosols, Limited Quantity Aerosols, Limited 14.2. UN proper shipping

> Quantity, 2.1, Quantity

14.3. Transport hazard **DOT Hazard Class: 2.1 IMDG: 2.1** Air Class: 2.1

class(es)

14.4. Packing group Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA)

All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification A B1

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: Yes



SDS Revision Date: 08/23/2018

Reactive: No

Immediate (Acute): No Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous:

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Butane

Propane

Propane, 2-methyl-

Penn RTK Substances (>1%):

Butane

Propane

Propane, 2-methyl-

SDS Revision Date:

LIGHTHOUSE for the BLIND ST. LOUIS, MO.

08/23/2018

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document