

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity

Power Spray Tool Aerosol

Alternate Names

Specification: SAE-AS22805
LHB Part Number: 0894---000
National Stock Number: 4940-00-803-6444
CAGE Code: 1A864

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See product label.

Application Method

See product label.

1.3. Details of the supplier of the safety data sheet

Company Name

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No.

(800) 633-8253 (PERS)

Customer Service: LHB Industries

(314) 423-4333

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Liquified Gas;H280

Contains gas under pressure; may explode if heated.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Warning

H280 Contains gas under pressure; may explode if heated.

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



May displace oxygen and cause rapid suffocation.

[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

P410+403 Protect from sunlight. Store in a well ventilated place.

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1,1,2-Tetrafluoroethane (HFC-134a) CAS Number: 0000811-97-2	100	Liquified Gas;H280 Simple Asphyxiant	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Get medical attention if frost bitten by liquid or if irritation occurs.

Ingestion

NA

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



4.2. Most important symptoms and effects, both acute and delayed

Overview

WARNING!

Liquid and gas under pressure, overheating and over-pressurizing may cause gas release or rupturing of container. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Vapor reduces oxygen available for breathing and is heavier than air. Harmful if inhaled and may cause heart irregularities, unconsciousness or death. Liquid contact with eyes or skin may cause frostbite.

Potential Health Effects:

Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material. As with most liquefied gases, contact with rapidly volatilizing liquid or cold vapor can cause frostbite to any tissue. High vapor concentration are irritating to the eyes and respiratory tract and may result in central nervous system effects such as headache, dizziness, anesthesia, drowsiness, and in severe exposure, loss of consciousness and death. The dense vapor of the material may reduce the available oxygen for breathing and produce symptoms such as headache, dizziness, drowsiness, cyanosis and lack of muscle control followed by collapse. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation of this material may cause an increase in sensitivity of the heart to adrenaline, which could result in irregular or rapid heartbeats and reduced heart function. Workers with heart disease or compromised heart function should limit exposure to this material. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Use media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrogen fluoride, hydrogen chloride, carbon monoxide carbon dioxide and chlorine.

5.3. Advice for fire-fighters

FIRE FIGHTING EQUIPMENT: Fire fighters should wear full protective equipment, and have self-contained breathing apparatus available. **SPECIAL PROCEDURES:** Use water to cool containers exposed to a fire.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid inhalation. Use good ventilation. Read entire label before using and follow all label directions.

Dispose of in accordance with applicable Federal, State & Local regulations. Remove ignition sources and work with non-sparking tools. Use oil absorbent materials.

Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Exhaust vapors outdoors. Do not smoke or operate internal combustion engines. Remove flames and heating elements.

7. Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat sparks, and open flame. Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Finely divided metals. Can react violently if in contact with alkali or alkaline earth metals such as sodium, potassium or barium.

Category NFPA 30B Level 2 Aerosol

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

See product label.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000811-97-2	1,1,1,2-Tetrafluoroethane (HFC-134a)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000811-97-2		OSHA	Select Carcinogen: No

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



	1,1,1,2-Tetrafluoroethane (HFC-134a)	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

- Respiratory** If personal exposure cannot be controlled to below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust that may be generated from this product, underlying paint, or the abrasive.
- Eyes** Use safety glasses with side shields or chemical goggles. If exposure causes eye discomfort, use a full-face respirator.
- Skin** Wear overalls to keep skin contact to a minimum. Chemical resistant gloves may be needed for long term skin exposure.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Colorless Liquefied Gas
Odor	Faint Ether
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	NA
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (Pa)	96.16 psia @ 77F
Vapor Density	3.25 (Heavier than Air)
Specific Gravity	1.21 @ 77F
Solubility in Water	Slight

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Density	10.09 lb/gal
VOC Content	0.0 by weight, 0 g/L
HAPS	None

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

10.5. Incompatible materials

Finely divided metals. Can react violently if in contact with alkali or alkaline earth metals such as sodium, potassium or barium.

10.6. Hazardous decomposition products

Hydrogen fluoride, hydrogen chloride, carbon monoxide carbon dioxide and chlorine.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
1,1,1,2-Tetrafluoroethane (HFC-134a) - (811-97-2)	No data available	No data available	No data available	No data available	No data available

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1,1,1,2-Tetrafluoroethane (HFC-134a) - (811-97-2)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not applicable	UN3159	UN3159
14.2. UN proper shipping name	Consumer Commodity	1,1,1,2-Tetrafluoroethane, 2.2	1,1,1,2-Tetrafluoroethane, 2.2
14.3. Transport hazard class(es)	DOT Hazard Class: ORM-D	IMDG: 2.2	Air Class: 2.2
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	A
US EPA Tier II Hazards	Fire: No Sudden Release of Pressure: Yes Reactive: No Immediate (Acute): No Delayed (Chronic): No

Safety Data Sheet

Power Spray Tool Aerosol

SDS Revision Date:

08/23/2018



EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

N.J. RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Penn RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H280 Contains gas under pressure; may explode if heated.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document