



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

### 1. Identification

#### 1.1. Product identifier

**Product Identity**

Skilcraft Power Duster, 10 oz

**Alternate Names**

Skilcraft Power Duster, 10 oz  
LHB Part Number: 0894---010  
National Stock Number: 7930-01-398-2473  
CAGE Code: 0FTT5

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

See Product Label

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

LHB Industries  
8833 Fleischer Place  
Berkeley, MO 63134

**Emergency**

**24 hour Emergency Telephone No.**

(800) 633-8253 (PERS)

**Customer Service: LHB Industries**

(314) 423-4333

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222

Extremely flammable aerosol.

Press. Gas;H280

Contains gas under pressure; may explode if heated.

STOT SE 3;H336

May cause drowsiness or dizziness.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

#### 2.2. Label elements



**Danger**



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H336 May cause drowsiness and dizziness.  
May displace oxygen and cause rapid suffocation.  
Pressurized container: May burst if heated.

### [Prevention]

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust, fume, gas, mist, vapors, spray.  
P271 Use only outdoors or in a well-ventilated area.

### [Response]

P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.

### [Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C , 122 °F.

### [Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1-Difluoroethane CAS Number: 0000075-37-6	100	Flam. Gas 1;H220 Liquified Gas;H280 STOT SE 3;H336 Simple Asphyxiant	----

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

## Section 4. First aid measures

### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

**Inhalation** May cause drowsiness or dizziness.

## Section 5. Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sup>2</sup>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrofluoric acid and carbonyl halides  
Keep away from heat, sparks, open flames, and other ignition sources - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Avoid breathing dust, fume, gas, mist, vapors, spray.

### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

**ERG Guide No.** 115



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

### Section 6. Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

**6.2. Environmental precautions**

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

**6.3. Methods and material for containment and cleaning up**

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

### Section 7. Handling and storage

**7.1. Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]

**7.2. Conditions for safe storage, including any incompatibilities**

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong alkalis or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]

**7.3. Specific end use(s)**

No data available.

### Section 8. Exposure controls / personal protection

**8.1. Control parameters**

**Exposure**

CAS No.	Ingredient	Source	Value
0000075-37-6	1,1-Difluoroethane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

### 8.2. Exposure controls

<b>Respiratory</b>	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
<b>Eyes</b>	Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.
<b>Skin</b>	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.
<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
<b>Other Work Practices</b>	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

## Section 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Color: Clear, Colorless	Physical State: Liquid/Gas
<b>Odor</b>	Slight Ethereal Odor	
<b>Odor threshold</b>	Not determined	
<b>pH</b>	Not Measured	
<b>Melting point / freezing point</b>	Not Measured	
<b>Initial boiling point and boiling range</b>	Not Measured	
<b>Flash Point</b>	-58 F (Estimated)	
<b>Evaporation rate (Ether = 1)</b>	Not Measured	
<b>Flammability (solid, gas)</b>	Not Applicable	
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 3.9% (vol.) Gas in air <b>Upper Explosive Limit:</b> 16.9% (vol.) Gas in air	
<b>Vapor pressure (Pa)</b>	62.5 PSIG @ 70 F	
<b>Vapor Density</b>	2.4 ( Heavier than Air )	
<b>Relative Density</b>	0.909 ( 7.58 lb/gal )	
<b>Solubility in Water</b>	0.28% @ 70 F	
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured	
<b>Auto-ignition temperature</b>	Not Measured	
<b>Decomposition temperature</b>	Not Measured	
<b>Viscosity (cSt)</b>	Not Measured	
<b>VOC Content</b>	0% by wt, 0 g/L	



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

<b>Maximum Incremental Reactivity</b>	Not Measured
<b>HAPS (lbs/gal)</b>	0.0
<b>HAPS (lbs/gal of Solids)</b>	0.0
<b>HAPS (lbs/lb of Solids)</b>	0.0
<b>% Volatile (by volume)</b>	Not Measured

### 9.2. Other information

No other relevant information.

## Section 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Do not expose to heat or store at temperature above 120°F

### 10.5. Incompatible materials

Strong alkalis or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers.

### 10.6. Hazardous decomposition products

Hydrofluoric acid and carbonyl halides

## Section 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1,1-Difluoroethane - (75-37-6)	No data available	No data available	No data available	No data available	No data available

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000075-37-6	1,1-Difluoroethane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## Section 12. Ecological information

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
1,1-Difluoroethane - (75-37-6)	Not Available	Not Available	Not Available



# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## Section 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## Section 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	Not Applicable	UN1030	UN1030
<b>14.2. UN proper shipping name</b>	Qualifies for DOT SP11516 exemption	1,1-Difluoroethane	1,1-Difluoroethane
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>IMDG:</b> 2.1 <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> 2.1 <b>Sub Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No;		
<b>14.6. Special precautions for user</b>	This material Qualifies for DOT SP11516.		

## Section 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.





# Safety Data Sheet

## Skilcraft Power Duster, 10 oz

Revision Date: 03/13/2023

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### Section 16. Other information

**Revision Date** 01/11/2022

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H336 May cause drowsiness and dizziness.

**IMPORTANT NOTE:** This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document