



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

1. Identification

1.1. Product identifier

Product Identity

Corrosion Preventive Compound, Aerosol

Alternate Names

Corrosion Preventive Compound, Aerosol,
Specification: MIL-DTL-85054D(AS), TYPE I, Class
CO₂
LHB Part Number: 0944---000
National Stock Number: 8030-01-347-0980
CAGE Code: 0FTT5 and 1A864
Contract Number: SPE8EG-16-D-0011

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency

24 hour Emergency Telephone No.

(800) 633-8253 (PERS)

Customer Service: LHB Industries

(314) 423-4333

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222

Extremely flammable aerosol.

Press. Gas;H280

Contains gas under pressure; may explode if heated.

Eye Dam. 2A;H319

Causes serious eye irritation.

Repr. 2;H361D

Suspected of damaging the unborn child.

STOT SE 3;H336

May cause drowsiness or dizziness.

STOT RE 1;H372

Causes damage to organs through prolonged or repeated exposure. Specific Target
Organs: (central nervous system central nervous system)

Asp. Tox. 1;H304

May be fatal if swallowed and enters airways.

Aquatic Acute 3;H402

Harmful to aquatic life.

Aquatic Chronic 3;H412

Harmful to aquatic life with long lasting effects.




Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

2.2. Label elements



Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Pressurized container: May burst if heated.

[Prevention]

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust, fume, gas, mist, vapors, spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313 IF exposed or concerned: Get medical advice or attention.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical attention.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

P337+313 If eye irritation persists: Get medical advice or attention.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 0000067-64-1	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Isopropyl Alcohol CAS Number: 0000067-63-0	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Stoddard solvent CAS Number: 0008052-41-3	5 - 10	STOT RE 1;H372 Asp. Tox. 1;H304	----
Acrylic polymer CAS Number: Proprietary	5 - 10	Not Classified	----
Toluene CAS Number: 0000108-88-3	5 - 10	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	----
Carbon dioxide CAS Number: 0000124-38-9	1 - 5	Press. Gas;H280 Simple Asphyxiant	----
Barium dinonylnaphthalenesulfonate CAS Number: 0025619-56-1	1 - 5	Acute Tox. 4;H302 Skin Irrit. 3;H316	----
Solvent naphtha (petroleum), medium aliphatic CAS Number: 0064742-88-7	1 - 5	STOT RE 1;H372 Asp. Tox. 1;H304	----

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.</p>
Inhalation	May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Eyes	Causes serious eye irritation.
Skin	Causes mild skin irritation. (Note: this GHS classification was not adopted by US OSHA).

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Carbon dioxide and carbon monoxide
Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing dust, fume, gas, mist, vapors, spray.
Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

FIRE FIGHTING EQUIPMENT: Fire fighters should wear full protective equipment, and have self-contained breathing apparatus available.

SPECIAL PROCEDURES: Use water to cool containers exposed to a fire.

Self-extinguishing. Does not hold a flame



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

ERG Guide No. ---

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Avoid inhalation. Use good ventilation. Read entire label before using and follow all label directions.

Dispose of in accordance with applicable Federal, State & Local regulations. Remove ignition sources and work with non-sparking tools. Use oil absorbent materials.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Keep out of reach of children. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: keep area ventilated- do not smoke- extinguish all flames, pilot lights, and heaters- turn off stoves, electric tools and appliances, and any other source of ignition. Consult NFPA code. Use approved bonding and grounding procedures. Do not take internally.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Oxidizing agents, strong acids.

Flammable Liquid, Class IB

Check section 2.2 (GHS Label Elements) for further details. - [Storage]

7.3. Specific end use(s)

See Product Label

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m ³) STEL 500 ppm
		ACGIH	TWA: 200 ppm STEL: 400 ppm
		NIOSH	TWA 400 ppm (980 mg/m ³) STEL: 500 ppm (1225 mg/m ³)



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m ³) STEL 2400 mg/m ³
		ACGIH	TWA: 500 ppm STEL: 750 ppm
		NIOSH	250 ppm (590 mg/m ³) TWA
0000108-88-3	Toluene	OSHA	TWA (OSHA) 200 ppm C 300 ppm 500 ppm (10-minute maximum peak) STEL 150 ppm
		ACGIH	TWA: 20 ppm
		NIOSH	TWA 100 ppm (375 mg/m ³) STEL: 150 ppm (560 mg/m ³)
0000124-38-9	Carbon dioxide	OSHA	TWA 5000 ppm (9000 mg/m ³)
		ACGIH	TWA: 5000 ppm Ceiling: 15000 ppm
		NIOSH	TWA 5000 ppm (9000 mg/m ³) STEL: 30,000 ppm (54,000 mg/m ³)
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m ³)
		ACGIH	TWA: 290 mg/m ³ STEL: 580 mg/m ³
		NIOSH	TWA 350 mg/m ³ C 1800 mg/m ³ [15-minute]
0025619-56-1	Barium dinonylnaphthalenesulfonate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
Proprietary	Acrylic polymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

8.2. Exposure controls

Respiratory

If personal exposure cannot be controlled to below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust that may be generated from this product, underlying paint, or the abrasive.

Eyes

Use safety glasses with side shields or chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin

Wear overalls to keep skin contact to a minimum. Chemical resistant gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Color: Blue Physical State: Liquid
Odor	Solvent
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	N/A
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: ND Upper Explosive Limit: ND
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Relative Density	0.89 Density 8.35 LBS/GAL
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC Content	384g/L (3.20 lb/gal)
Maximum Incremental Reactivity	0.820

9.2. Other information

No other relevant information.

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

No data available.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

10.5. Incompatible materials

Oxidizing agents, strong acids.

10.6. Hazardous decomposition products

Carbon dioxide and carbon monoxide

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available
Isopropyl Alcohol - (67-63-0)	5,840.00, Rat - Category: NA	16,400.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available	No data available
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA	No data available
Acrylic polymer - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Toluene - (108-88-3)	5,580.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Carbon dioxide - (124-38-9)	No data available	No data available	No data available	No data available	No data available
Barium dinonylnaphthalenesulfonate - (25619-56-1)	No data available	No data available	No data available	No data available	No data available
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	6,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

		ACGIH	A4
0000067-64-1	Acetone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
0000108-88-3	Toluene	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	A4
0000124-38-9	Carbon dioxide	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0025619-56-1	Barium dinonylnaphthalenesulfonate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
Proprietary	Acrylic polymer	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure	3	May cause drowsiness or dizziness.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

STOT-single exposure	---	Not Applicable
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	1	May be fatal if swallowed and enters airways.

Section 12. Ecological information

12.1. Toxicity

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00 (96 hr), Pseudokirchneriella subcapitata
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	Not Available	Not Available
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available
Acrylic polymer - (Proprietary)	Not Available	Not Available	Not Available
Toluene - (108-88-3)	5.50, Oncorhynchus kisutch	3.78, Ceriodaphnia dubia	10.00 (72 hr), Skeletonema costatum
Carbon dioxide - (124-38-9)	Not Available	Not Available	Not Available
Barium dinonylnaphthalenesulfonate - (25619-56-1)	Not Available	Not Available	Not Available
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	800.00, Pimephales promelas	100.00, Daphnia magna	450.00 (96 hr), Selenastrum capricornutum

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state, and local regulations when disposing of this substance.

Section 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1950	UN1950	UN1950
14.2. UN proper shipping name	UN1950, Aerosols, Limited Quantity, 2.1, NA	Aerosols, Limited Quantity	Aerosols, Limited Quantity
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1	IMDG: 2.1 Sub Class: Not Applicable	Air Class: 2.1
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No;		
14.6. Special precautions for user	No further information		

Section 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
EPCRA 302 Extremely Hazardous: To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.	
EPCRA 313 Toxic Chemicals: Barium dinonylnaphthalenesulfonate Ethylbenzene Isopropyl Alcohol Toluene	
Proposition 65 - Carcinogens (>0.0%): Cumene Ethylbenzene	



Safety Data Sheet

Corrosion Preventive Compound, Aerosol

Revision Date: 02/21/2023

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

Toluene

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Cumene, Ethylbenzene], which are known to the State of California to cause cancer, and [Toluene], which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16. Other information

Revision Date 02/21/2023

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document